

Permabond UV6160

Safety Data Sheet

Classification complies with OSHA Hazard Communication Standard (29 CFR 1910.1200) and is consistent with the provisions of the United Nations Globally Harmonized System of Classification and Labeling of Chemicals (GHS)

1. Identification

1.1. Product identifier

Product name **Permabond UV6160**

1.2. Relevant identified uses of the substance or mixture and uses advised against

Intended use **Adhesive**

Identified Uses	Industrial	Professional	Consumer
Use	✓	✓	-

1.3. Details of the supplier of the safety data sheet

Name **Permabond Engineering Adhesives**
 Full address **Niederkasseler Lohweg 18**
 District and Country **40547 Düsseldorf Germany**
 Tel. **+44 (0)1962 711 661**
 e-mail address of the competent person responsible for the Safety Data Sheet **info.europe@permabond.com**

Supplier: **Permabond LCC**
14 Robinson Street
Pottstown, PA 19464, USA
tel 732-868-1372 OR 800-640-7599
www.permabond.com

1.4. Emergency telephone number

For urgent inquiries refer to **Medical: Poison Control Center 866-827-6282 (toll free) or 303-389-1109**
Transport: CHEMTREC 800-424-9300 (toll free) or 1-703-741-5970

2. Hazards identification

2.1. Classification of the substance or mixture

Classification and Hazard Statement	
Eye irritation, category 2	Causes serious eye irritation.
Skin irritation, category 2	Causes skin irritation.
Specific target organ toxicity - single exposure, category 3	May cause respiratory irritation.
Skin sensitization, category 1A	May cause an allergic skin reaction.

Hazard pictograms:



Signal words: **Warning**

Hazard statements:

H319	Causes serious eye irritation.
H315	Causes skin irritation.
H335	May cause respiratory irritation.
H317	May cause an allergic skin reaction.

Precautionary statements:

Prevention:

P261	Avoid breathing vapors or aerosols.
P280	Wear protective gloves / eye protection / face protection.

Permabond UV6160

2. Hazards identification ... / >>

P271	Use only outdoors or in a well-ventilated area.
P264	Wash contaminated skin thoroughly after handling.
P272	Contaminated work clothing should not be allowed out of the workplace.
Response:	
P305+P351+P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P312	Call a POISON CENTER / doctor / . . . / if you feel unwell.
P333+P313	If skin irritation or rash occurs: Get medical advice / attention.
P337+P313	If eye irritation persists: Get medical advice / attention.
P304+P340	IF INHALED: Remove person to fresh air and keep comfortable for breathing.
P302+P352	IF ON SKIN: Wash with plenty of soap and water.
P362+P364	Take off contaminated clothing and wash it before reuse.
P363	Wash contaminated clothing before reuse.
Storage:	
P403+P233	Store in a well-ventilated place. Keep container tightly closed.
P405	Store locked up.
Disposal:	
P501	Dispose of the product according to current regulations.

2.2. Other hazards

No other hazards known.

3. Composition/information on ingredients

3.2. Mixtures

Contains:

Identification	x = Conc. %	Classification:
ISOBORNYL ACRYLATE		
	$30 \leq x < 60$	Skin sensitization, category 1A H317
EC	227-561-6	
CAS	5888-33-5	
REACH Reg.	01-2119957862-25-XXXX	
2-HYDROXYETHYL METHACRYLATE		
INDEX	607-124-00-X $10 \leq x < 30$	Eye irritation, category 2 H319, Skin irritation, category 2 H315, Skin sensitization, category 1 H317
EC	212-782-2	
CAS	868-77-9	
REACH Reg.	01-2119490169-29-XXXX	
METHACRYLIC ACID		
INDEX	607-088-00-5 $1 \leq x < 3$	Flammable liquid, category 4 H227, Acute toxicity, category 3 H311, Acute toxicity, category 4 H302, Acute toxicity, category 4 H332, Skin corrosion, category 1A H314, Specific target organ toxicity - single exposure, category 3 H335
EC	201-204-4	
CAS	79-41-4	
REACH Reg.	01-2120741502-64-XXXX	
MALEIC ACID		
	$1 \leq x < 5$	Acute toxicity, category 4 H302, Eye irritation, category 2 H319, Skin irritation, category 2 H315, Specific target organ toxicity - single exposure, category 3 H335, Skin sensitization, category 1 H317
EC	203-742-5	
CAS	110-16-7	
REACH Reg.	01-2119488705-25-XXXX	
ETHYL PHENYL(2,4,6-TRIMETHYLBENZOYL)PHOSPHINATE		
	$1 \leq x < 2.5$	Skin sensitization, category 1B H317
EC	282-810-6	
CAS	84434-11-7	
REACH Reg.	01-2119987994-10-XXXX	

* There is a batch to batch variation.

The full wording of hazard (H) phrases is given in section 16 of the sheet.

Permabond UV6160**4. First-aid measures****4.1. Description of first aid measures**

In case of doubt or in the presence of symptoms contact a doctor and show him this document.

In case of more severe symptoms, ask for immediate medical aid.

EYES: Remove, if present, contact lenses if the situation allows you to do so easily. Wash immediately with plenty of water for at least 15 minutes, opening the eyelids fully. Get medical advice/attention.

SKIN: Take off immediately all contaminated clothing. Wash immediately and thoroughly with running water (and soap if possible). Get medical advice/attention. Avoid further contact with contaminated clothing.

INGESTION: Do not induce vomiting unless explicitly authorised by a doctor. Do not give anything by mouth to an unconscious person. Get medical advice/attention.

INHALATION: Remove victim to fresh air, away from the accident scene. In the event of respiratory symptoms (coughing, wheezing, breathing difficulty, asthma) keep the victim in a comfortable position for breathing. If necessary administer oxygen. If the subject stops breathing, administer artificial respiration. Get medical advice/attention.

Rescuer protection

It is good practice for rescuers lending support to a person who has been exposed to a chemical substance or to a mixture to wear personal protective equipment. The nature of such protection depends on the hazard level of the substance or mixture, on the type of exposure and on the extent of the contamination. In the absence of other more specific indications, use of disposable gloves in the event of possible contact with body fluids is recommended. For the type of PPE suitable for the characteristics of the substance or mixture, see section 8.

4.2. Most important symptoms and effects, both acute and delayed

Specific information on symptoms and effects caused by the product are unknown.

DELAYED EFFECTS: Based on the information currently available, there are no known cases of delayed effects following exposure to this product.

4.3. Indication of any immediate medical attention and special treatment needed

If symptoms occur, whether acute or delayed, consult a doctor.

Means to have available in the workplace for specific and immediate treatment

Running water for skin and eye wash.

5. Fire-fighting measures**5.1. Extinguishing media****SUITABLE EXTINGUISHING EQUIPMENT**

The extinguishing equipment should be of the conventional kind: carbon dioxide, foam, powder and water spray.

UNSUITABLE EXTINGUISHING EQUIPMENT

None in particular.

5.2. Special hazards arising from the substance or mixture**HAZARDS DUE TO EXPOSURE IN THE EVENT OF FIRE**

Avoid breathing combustion products, carbon monoxide (CO), carbon dioxide (CO₂), and nitric oxides (NO_x).

5.3. Advice for firefighters**GENERAL INFORMATION**

Use jets of water to cool the containers to prevent product decomposition and the development of substances potentially hazardous for health. Always wear full fire prevention gear. Collect extinguishing water to prevent it from draining into the sewer system. Dispose of contaminated water used for extinction and the remains of the fire according to applicable regulations.

SPECIAL PROTECTIVE EQUIPMENT FOR FIRE-FIGHTERS

Normal fire fighting clothing i.e. fire kit (BS EN 469), gloves (BS EN 659) and boots (HO specification A29 and A30) in combination with self-contained open circuit positive pressure compressed air breathing apparatus (BS EN 137).

6. Accidental release measures**6.1. Personal precautions, protective equipment and emergency procedures**

Block the leakage if there is no hazard.

Permabond UV6160

6. Accidental release measures ... / >>

Wear suitable protective equipment (including personal protective equipment referred to under Section 8 of the safety data sheet) to prevent any contamination of skin, eyes and personal clothing. These indications apply for both processing staff and those involved in emergency procedures.

6.2. Environmental precautions

The product must not penetrate into the sewer system or come into contact with surface water or ground water.

6.3. Methods and material for containment and cleaning up

Collect the leaked product into a suitable container. Evaluate the compatibility of the container to be used, by checking section 10. Absorb the remainder with inert absorbent material.

Make sure the leakage site is well aired. Contaminated material should be disposed of in compliance with the provisions set forth in point 13.

6.4. Reference to other sections

Any information on personal protection and disposal is given in sections 8 and 13.

7. Handling and storage

7.1. Precautions for safe handling

Keep away from heat, sparks and naked flames; do not smoke or use matches or lighters. Without adequate ventilation, vapours may accumulate at ground level and, if ignited, catch fire even at a distance, with the danger of backfire. Avoid bunching of electrostatic charges. Do not eat, drink or smoke during use. Remove any contaminated clothes and personal protective equipment before entering places in which people eat. Avoid leakage of the product into the environment.

7.2. Conditions for safe storage, including any incompatibilities

Store only in the original container. Store in a cool and well ventilated place, keep far away from sources of heat, naked flames and sparks and other sources of ignition. Keep containers away from any incompatible materials, see section 10 for details.

7.3. Specific end use(s)

Information not available

8. Exposure controls/personal protection

8.1. Control parameters

Regulatory references:

USA	NIOSH-REL	NIOSH publication No. 2005-149, 3th printing, 2007.
USA	CAL/OSHA-PEL	California Division of Occupational Safety and Health (Cal-OSHA) Permissible Exposure Limits (PELs).

METHACRYLIC ACID

Threshold Limit Value

Type	Country	TWA/8h		STEL/15min		Remarks / Observations
		mg/m ³	ppm	mg/m ³	ppm	
CAL/OSHA	USA	70	20			SKIN
NIOSH	USA	70	20			SKIN

Legend:

(C) = CEILING ; INHAL = Inhalable Fraction ; RESP = Respirable Fraction ; THORA = Thoracic Fraction.

8.2. Exposure controls

As the use of adequate technical equipment must always take priority over personal protective equipment, make sure that the workplace is well aired through effective local aspiration. Personal protective equipment must comply with current regulations.

HAND PROTECTION

Protect hands with category III work gloves.

The following should be considered when choosing work glove material (OSHA 29 CFR 1910.138): compatibility, degradation, permeability time.

The work gloves' resistance to chemical agents should be checked before use, as it can be unpredictable. The gloves' wear time depends on the duration and type of use.

SKIN PROTECTION

Wear category I professional long-sleeved overalls and safety footwear. Wash body with soap and water after removing protective clothing.

Permabond UV6160

8. Exposure controls/personal protection ... / >>

EYE PROTECTION

Wear airtight protective goggles (OSHA 29 CFR 1910.133).

RESPIRATORY PROTECTION

If the threshold value (e.g. TLV-TWA) is exceeded for the substance or one of the substances present in the product, wear a mask with a NIOSH certified filter, whose class must be chosen according to the limit of use concentration (NIOSH 42 CFR 84, OSHA 29 CFR 1910.134). In the presence of gases or vapours of various kinds and/or gases or vapours containing particulate (aerosol sprays, fumes, mists, etc.) combined filters are required.

Respiratory protection devices must be used if the technical measures adopted are not suitable for restricting the worker's exposure to the threshold values considered. The protection provided by masks is in any case limited.

If the substance considered is odourless or its olfactory threshold is higher than the corresponding TLV-TWA and in the case of an emergency, wear open-circuit compressed air breathing apparatus or external air-intake breathing apparatus. For a correct choice of respiratory protection device, see standard NIOSH 42 CFR 84, OSHA 29 CFR 1910.134.

ENVIRONMENTAL EXPOSURE CONTROLS

The emissions generated by manufacturing processes, including those generated by ventilation equipment, should be checked to ensure compliance with environmental standards.

Product residues must not be indiscriminately disposed of with waste water or by dumping in waterways.

9. Physical and chemical properties

9.1. Information on basic physical and chemical properties

Properties	Value	Information
Appearance	liquid	
Colour	colourless	
Odour	characteristic	
Odour threshold	not available	
pH	not available	Reason for missing data: substance/mixture is non-soluble (in water)
Melting point / freezing point	not available	
Initial boiling point	not available	
Boiling range	not available	
Flash point	> 100 °C (212 °F)	
Evaporation rate	not available	
Flammability	not available	
Lower explosive limit	not available	
Upper explosive limit	not available	
Vapour pressure	not available	
Vapour density	not available	
Relative density	1.1	
Solubility	not available	
Partition coefficient: n-octanol/water	not available	
Auto-ignition temperature	not available	
Decomposition temperature	not available	
Viscosity	not available	
Explosive properties	not available	
Oxidising properties	not available	

9.2. Other information

Information not available

10. Stability and reactivity

10.1. Reactivity

There are no particular risks of reaction with other substances in normal conditions of use.

10.2. Chemical stability

The product is stable in normal conditions of use and storage.

10.3. Possibility of hazardous reactions

No hazardous reactions are foreseeable in normal conditions of use and storage.

10.4. Conditions to avoid

Permabond UV6160

10. Stability and reactivity ... / >>

None in particular. However the usual precautions used for chemical products should be respected.

10.5. Incompatible materials

Information not available

10.6. Hazardous decomposition products

In the event of thermal decomposition or fire, gases and vapours that are potentially dangerous to health may be released.

11. Toxicological information

In the absence of experimental data for the product itself, health hazards are evaluated according to the properties of the substances it contains, using the criteria specified in the applicable regulation for classification. It is therefore necessary to take into account the concentration of the individual hazardous substances indicated in section 3, to evaluate the toxicological effects of exposure to the product.

11.1. Information on toxicological effects

Metabolism, toxicokinetics, mechanism of action and other information

Information not available

Information on likely routes of exposure

Information not available

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Information not available

Interactive effects

Information not available

ACUTE TOXICITY

MALEIC ACID	
LD50 (Oral):	2870 mg/kg
LD50 (Dermal):	> 400 mg/kg
LC50 (Inhalation mists/powders):	> 0.72 mg/l/1h

2-HYDROXYETHYL METHACRYLATE	
LD50 (Oral):	> 5000 mg/kg
LD50 (Dermal):	> 5000 mg/kg

ISOBORNYL ACRYLATE	
LD50 (Oral):	4350 mg/kg
LD50 (Dermal):	> 3000 mg/kg

METHACRYLIC ACID	
LD50 (Oral):	1320 mg/kg
LD50 (Dermal):	750 mg/kg
LC50 (Inhalation vapours):	7.1 mg/l/4h

ETHYL PHENYL(2,4,6-TRIMETHYLBENZOYL)PHOSPHINATE	
LD50 (Oral):	> 5000 mg/kg
LD50 (Dermal):	> 2000 mg/kg

SKIN CORROSION / IRRITATION

Causes skin irritation

SERIOUS EYE DAMAGE / IRRITATION

Causes serious eye irritation

RESPIRATORY OR SKIN SENSITISATION

Permabond UV6160

11. Toxicological information ... / >>

Sensitising for the skin

GERM CELL MUTAGENICITY

Does not meet the classification criteria for this hazard class

CARCINOGENICITY

Does not meet the classification criteria for this hazard class

REPRODUCTIVE TOXICITY

Does not meet the classification criteria for this hazard class

STOT - SINGLE EXPOSURE

May cause respiratory irritation

STOT - REPEATED EXPOSURE

Does not meet the classification criteria for this hazard class

ASPIRATION HAZARD

Does not meet the classification criteria for this hazard class

12. Ecological information

This product is dangerous for the environment and highly toxic for aquatic organisms. In the long term, it has negative effects on the aquatic environment.

12.1. Toxicity

MALEIC ACID

LC50 - for Fish	75 mg/l/96h
EC50 - for Crustacea	42.81 mg/l/48h
EC50 - for Algae / Aquatic Plants	74.32 mg/l/72h

2-HYDROXYETHYL METHACRYLATE

LC50 - for Fish	> 100 mg/l/96h
EC50 - for Crustacea	380 mg/l/48h
EC50 - for Algae / Aquatic Plants	836 mg/l/72h

ISOBORNYL ACRYLATE

LC50 - for Fish	0.704 mg/l/96h
EC50 - for Algae / Aquatic Plants	1.98 mg/l/72h
Chronic NOEC for Fish	0.431 mg/l

Chronic NOEC for Crustacea 0.092 mg/l

Chronic NOEC for Algae / Aquatic Plants 0.405 mg/l

METHACRYLIC ACID

LC50 - for Fish	85 mg/l/96h
EC50 - for Crustacea	> 130 mg/l/48h

Permabond UV6160

12. Ecological information ... / >>

EC50 - for Algae / Aquatic Plants	45 mg/l/72h
ETHYL PHENYL(2,4,6-TRIMETHYLBENZOYL)PHOSPHINATE	
LC50 - for Fish	1.89 mg/l/96h
EC50 - for Crustacea	2.26 mg/l/48h
EC50 - for Algae / Aquatic Plants	1.01 mg/l/72h
Chronic NOEC for Fish	> 1.29 mg/l

12.2. Persistence and degradability

2-HYDROXYETHYL METHACRYLATE	Rapidly degradable
ISOBORNYL ACRYLATE	NOT rapidly degradable
METHACRYLIC ACID	Rapidly degradable
ETHYL PHENYL(2,4,6-TRIMETHYLBENZOYL)PHOSPHINATE	NOT rapidly degradable

12.3. Bioaccumulative potential

Information not available

12.4. Mobility in soil

ETHYL PHENYL(2,4,6-TRIMETHYLBENZOYL)PHOSPHINATE	
Partition coefficient: soil/water	3.37

12.5. Results of PBT and vPvB assessment

On the basis of available data, the product does not contain any PBT or vPvB in percentage \geq than 0,1%.

12.6. Other adverse effects

Information not available

13. Disposal considerations

13.1. Waste treatment methods

Reuse, when possible. Neat product residues should be considered special non-hazardous waste.
Disposal must be performed through an authorised waste management firm, in compliance with national and local regulations.
The management of waste arising from the use or dispersal of this product must be organised in accordance with occupational safety regulations. See section 8 for possible need for PPE.
CONTAMINATED PACKAGING
Contaminated packaging must be recovered or disposed of in compliance with national waste management regulations.

14. Transport information

14.1. UN number

ADR / RID, IMDG, IATA:	UN 3082
ADR / RID:	In accordance with Special Provision 375, this product, when is packed in receptacles of a capacity \leq 5Kg or 5L, is not submitted to ADR provisions.
IMDG:	In accordance with Section 2.10.2.7 of IMDG Code, this product, when is packed in receptacles of a capacity \leq 5Kg or 5L, is not submitted to IMDG Code provisions.

Permabond UV6160

14. Transport information ... / >>

IATA: In accordance with SP A197, this product, when is packed in receptacles of a capacity ≤ 5Kg or 5L, is not submitted to IATA dangerous goods regulations.

14.2. UN proper shipping name

ADR / RID: ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (ISOBORNYL ACRYLATE; ETHYL PHENYL(2,4,6-TRIMETHYLBENZOYL)PHOSPHINATE)
 IMDG: ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (ISOBORNYL ACRYLATE; ETHYL PHENYL(2,4,6-TRIMETHYLBENZOYL)PHOSPHINATE)
 IATA: ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (ISOBORNYL ACRYLATE; ETHYL PHENYL(2,4,6-TRIMETHYLBENZOYL)PHOSPHINATE)

14.3. Transport hazard class(es)

ADR / RID: Class: 9 Label: 9



IMDG: Class: 9 Label: 9



IATA: Class: 9 Label: 9



14.4. Packing group

ADR / RID, IMDG, IATA: III

14.5. Environmental hazards

ADR / RID: Environmentally Hazardous



IMDG: Marine Pollutant



IATA: Environmentally Hazardous



14.6. Special precautions for user

ADR / RID:	HIN - Kemler: 90	Limited Quantities: 5 lt	Tunnel restriction code: (-)
	Special provision: 274, 335, 375, 601		
IMDG:	EMS: F-A, S-F	Limited Quantities: 5 lt	
IATA:	Cargo:	Maximum quantity: 450 L	Packaging instructions: 964
	Passengers:	Maximum quantity: 450 L	Packaging instructions: 964
	Special provision:	A97, A158, A197, A215	

14.7. Transport in bulk according to Annex II of Marpol and the IBC Code

Information not relevant

15. Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

U.S. Federal Regulations

TSCA:
All components of this product are listed on US Toxic Substances Control Act (TSCA) Inventory or are exempt from the listing / notification

Permabond UV6160

15. Regulatory information ... / >>

requirements.

Clean Air Act Section 112(b):
No component(s) listed.

Clean Air Act Section 602 Class I Substances:
No component(s) listed.

Clean Air Act Section 602 Class II Substances:
No component(s) listed.

Clean Water Act – Priority Pollutants:
No component(s) listed.

Clean Water Act – Toxic Pollutants:
No component(s) listed.

DEA List I Chemicals (Precursor Chemicals):
No component(s) listed.

DEA List II Chemicals (Essential Chemicals):
No component(s) listed.

EPA List of Lists:
313 Category Code:
No component(s) listed.

EPCRA 302 EHS TPQ:
No component(s) listed.

EPCRA 304 EHS RQ:
No component(s) listed.

CERCLA RQ:
110-16-7 MALEIC ACID

EPCRA 313 TRI:
No component(s) listed.

RCRA Code:
No component(s) listed.

CAA 112 (r) RMP TQ:
No component(s) listed.

State Regulations

Massachusetts:
110-16-7 MALEIC ACID
79-41-4 METHACRYLIC ACID

Minnesota:
79-41-4 METHACRYLIC ACID

New Jersey:
110-16-7 MALEIC ACID
79-41-4 METHACRYLIC ACID

New York:
110-16-7 MALEIC ACID

Pennsylvania:
110-16-7 MALEIC ACID
79-41-4 METHACRYLIC ACID

California:
110-16-7 MALEIC ACID
79-41-4 METHACRYLIC ACID

Permabond UV6160

15. Regulatory information ... / >>

Proposition 65:

This product does not contain any substances know to the State of California to cause cancer, reproductive harm or birth defects.

International Regulations

Substances subject to exportation reporting pursuant to Regulation (EU) 649/2012:

None

Substances subject to the Rotterdam Convention:

None

Substances subject to the Stockholm Convention:

None

16. Other information

Text of hazard (H) indications mentioned in section 2-3 of the sheet:

H227	Combustible liquid.
H311	Toxic in contact with skin.
H302	Harmful if swallowed.
H332	Harmful if inhaled.
H314	Causes severe skin burns and eye damage.
H319	Causes serious eye irritation.
H315	Causes skin irritation.
H335	May cause respiratory irritation.
H317	May cause an allergic skin reaction.
H400	Very toxic to aquatic life.
H410	Very toxic to aquatic life with long lasting effects.
H411	Toxic to aquatic life with long lasting effects.

LEGEND:

- 313 CATEGORY CODE: Emergency Planning and Community Right-to Know Act Section 313 Category Code
- ADR: European Agreement concerning the carriage of Dangerous goods by Road
- ATE: Acute Toxicity Estimate
- CAA 112 @ RMP TQ: Risk Management Plan Threshold Quantity (Clean Air Act Section 112®)
- CAS: Chemical Abstract Service Number
- CE50: Effective concentration (required to induce a 50% effect)
- CERCLA RQ: Reportable Quantity (Comprehensive Environment Response, Compensation, and Liability Act)
- CLP: Regulation (EC) 1272/2008
- DEA: Drug Enforcement Administration
- EmS: Emergency Schedule
- EPA: US Environmental Protection Agency
- EPCRA: Emergency Planning and Community Right-to Know Act
- EPCRA 302 EHS TPQ: Extremely Hazardous Substance Threshold Planning Quantity (Section 302 Category Code)
- EPCRA 304 EHS RQ: Extremely Hazardous Substance Reportable Quantity (Section 304 Category Code)
- EPCRA 313 TRI: Toxics Release Inventory (Section 313 Category Code)
- GHS: Globally Harmonized System of classification and labeling of chemicals
- IATA DGR: International Air Transport Association Dangerous Goods Regulation
- IC50: Immobilization Concentration 50%
- IMDG: International Maritime Code for dangerous goods
- IMO: International Maritime Organization
- LC50: Lethal Concentration 50%
- LD50: Lethal dose 50%
- OEL: Occupational Exposure Level
- PEL: Predicted exposure level
- RCRA Code: Resource Conservation and Recovery Act Code
- REACH: Regulation (EC) 1907/2006
- REL: Recommended exposure limit
- RID: Regulation concerning the international transport of dangerous goods by train
- TLV: Threshold Limit Value
- TLV CEILING: Concentration that should not be exceeded during any time of occupational exposure.
- TSCA: Toxic Substances Control Act
- TWA: Time-weighted average exposure limit
- TWA STEL: Short-term exposure limit
- VOC: Volatile organic Compounds
- WHMIS: Workplace Hazardous Materials Information System.

GENERAL BIBLIOGRAPHY:

- GHS rev. 3

Permabond UV6160**16. Other information ... / >>**

- The Merck Index. 10th Edition
- Handling Chemical Safety
- Niosh - Registry of Toxic Effects of Chemical Substances
- INRS - Fiche Toxicologique (toxicological sheet)
- Patty - Industrial Hygiene and Toxicology
- N.I. Sax - Dangerous properties of Industrial Materials-7, 1989 Edition
- ECHA website
- Database of SDS models for chemicals - Ministry of Health and ISS (Istituto Superiore di Sanità) - Italy

- 6 NYCRR part 597
- Cal/OSHA website
- California Safe Drinking Water and Toxic Enforcement Act
- EPA website
- Hazard Communication Standard (HCS 2012)
- IARC website
- List Of Lists EPA: Consolidated List of Chemicals Subject to EPCRA, CERCLA and Section 112® of the Clean Air Act
- Massachusetts 105 CMR Department of public health 670.000: "Right to Know"
- Minnesota Chapter 5206 Department Of Labor and Industry Hazardous Substances, Employee "Right to Know".
- New Jersey Worker and Community Right to know Act N.J.S.A.
- NTP. 2011. Report on Carcinogens, 12th Edition.
- OSHA website
- Pennsylvania, Hazardous Substance List, Chapter 323

Note for users:

The information contained in the present sheet are based on our own knowledge on the date of the last version. Users must verify the suitability and thoroughness of provided information according to each specific use of the product.

This document must not be regarded as a guarantee on any specific product property.

The use of this product is not subject to our direct control; therefore, users must, under their own responsibility, comply with the current health and safety laws and regulations. The producer is relieved from any liability arising from improper uses.

Provide appointed staff with adequate training on how to use chemical products.

CALCULATION METHODS FOR CLASSIFICATION

Product classification derives from criteria established by the OSHA Hazard Communication Standard (HCS) (29 CFR 1910.1200), unless determined otherwise in Section 11 and 12. The data for evaluation of chemical-physical properties are reported in section 9.